

## **ADDITIONAL INSTALLED EQUIPMENT LIST**

<b>Description</b>	<b>Condition Rating</b>		
	<b>Very Good</b>	<b>Average</b>	<b>Minimum</b>
<b>RADIO TELEMETRY</b>			
Unit (RTU) (Master)	31,500	22,000	5,500
(Large)	7,500	3,440	860
(Small)	5,100	2,090	520
<b>Cathodic Protection Unit</b>			
with Rectifier	1,360	690	170
with Solar Panels	6,250	2,580	640
<b>Gas Meter Run</b>	3,880	2,120	630
<b>LACT Unit</b>	16,790	8,610	2,150
<b>Gas Booster Line</b>			
Compressor (15-30 H.P.)	20,580	10,010	2,500
<b>In-Line Heater</b>	5,490	2,760	690
<b>Triplex Water Injection Pump</b>			
75 H.P. Electric Motor	17,920	9,260	2,120
<b>Chemical Pump</b>	990	490	220
<b>Recycle Pump</b>	1,030	640	160
<b>Free Water Knockouts</b>			
30" x 10'	3,700	2,220	560
4' x 10'	5,400	3,250	810
6' x 10'	6,250	3,740	930
8' x 10'	8,790	5,210	1,300
4' x 15'	5,790	3,470	870
6' x 15'	7,070	4,230	1,060
<b>Dehydrator</b>			
Average of All Sizes	13,610	7,920	1,980
<b>Wellheads</b>			
Flanged Wellhead (Total Value)*	4,770	1,720	600
Threaded Wellhead (Total Value)*	1,250	750	200
Flanged Wellhead (Differential)**	3,520	970	400
Flanged/Threaded Combo (Differential)**	2110	850	330
<b>Vapor Recovery System</b>	14,500	8,700	2,180
<b>Vapor Flare System (Enclosed Stack)</b>	10,000	6,000	1,500
<b>Sound Panels (Galvanized Steel):</b>			
Wall Panels (Padded 2' x 8' per sheet)	50	40	10
Roof Panels (Padded 2' x 8' per sheet)	50	40	10

*\*For use only with wells having dual wellheads on the same wellbore.*

*\*\*For use only in Basins where Threaded Wellheads are typical. (See VALUATION PROCEDURES.)*

<b>Description</b>	<b>Condition Rating</b>		
	<b>Very Good</b>	<b>Average</b>	<b>Minimum</b>
<b><u>Waste Oil Recycling Operations Only:</u></b>			
<b>Tank (1) 300 BBL</b>	5,890	2,940	1,350
<b>Separator 30" x 10' Vertical</b>	4,810	2,320	580
<b>Separator 24" x 10' Horizontal</b>	7,550	3,960	990